

# Hobbies

## WEEKLY

### CONTENTS


	Page
Block Toys in Wood	401
A Sliding Towel Rack	402
Lawns and their Making	403
Useful Pencil Box	404
Bricklaying for Beginners	405
Bedside Lamp & Clock	407
For Cyclist and Hiker	408
Realism in Model Work	408
Sturdy Garden Seat	409
Books to Read	410
'P.O.P.' is Here Again	411
Stamp Collecting	412
Block Toy Patterns	415

March 28th, 1951

Price Fourpence

Vol. III No. 2891

## HOW TO MAKE SMALL BLOCK TOYS IN WOOD



can be very quickly marked on to the wood. Do not forget to keep the pencil sharp during this operation. Fig. 2 shows the mudguards being glued in place. The construction of all three vehicles is exactly the same.

### Shaping

The next step is to round off all the edges to give a more streamlined appearance. This can best be done with a small rasp, but a sharp penknife will do almost as well. Having roughly rounded the edges you can now clean them up thoroughly with glasspaper. Fig. 3 shows how the body and mudguards will look after shaping.

### Painting

First give one coat of flat undercoating and then apply two thin coats of glossy enamel. The colours will, naturally, be bright; say, red or bright

**H**ERE is a suggestion for our fretwork enthusiasts who have small children with birthdays during the summer months. Simple cars are made up in block form so that they are easily assembled and painted. The shapes are designed to represent the real thing, without a great deal of intricate cutting or the addition of a lot of details.

These sturdy little toys are really intended for rough usage, and they are highly suitable, therefore, for the youngsters to pull about in the garden.

If you will turn to page 415 you will see three complete outlines—a saloon car, a tradesman's van and a two-seater coupé. The positions of the mudguards are dotted on in each case, and you will also notice that the same mudguards are suitable for each of the three designs. When marking the shapes on to wood remember that the grain of the wood must run in the direction shown by the arrows.

### Cutting Out the Parts

The wood suggested is odd  $\frac{1}{2}$  in. stuff.

The body of each car is made up of three pieces as shown in Fig. 1. The car we have chosen as an example is the two-

Full size patterns on  
page 415

seater, and the shape is carefully traced on to the wood three times. Two pieces will have the window openings cut out and the third piece can be solid for the sake of strength.

These three pieces are glued together and placed under a weight for a time until the glue has hardened. The mudguards are also cut from  $\frac{1}{2}$  in. wood. We suggest that a template be cut from card for each mudguard, and then any number




Fig. 1—How the bodies are made up



blue, and you could also introduce two shades of the same colour on each vehicle. Allow each coat to dry thoroughly before applying the next. This is absolutely essential with toys that are handled frequently.

The inside of the side windows and the windscreen can be painted black, while the radiator could be black with silver lines marked on. If you wish to add further detail you could paint on the door handles and headlamps. Alternatively,

the headlamps could be small circles of card cut out with scissors. Do not add too much detail, however, or the character of the cars will be destroyed. They are not intended to be models but merely sturdy toys.

### The Wheels

To save expense the wheels could be cut from  $\frac{1}{2}$  in. wood and the edges rounded off with a rasp. Many workers, however, are not keen on cutting their

own wheels because of the difficulty in getting them perfectly round. Suitable bakelite wheels,  $1\frac{1}{2}$  ins. diameter, are supplied by Hobbies Ltd. and cost 9d. per set of four. Postage and packing is, of course, extra. This will amount to  $2\frac{1}{2}$  d. per set.

Since the body is quite solid we suggest that you use fairly long screws—about 1 in.—which will hold the wheels securely in place. (403)




Fig. 2—Mudguards being glued into place





Fig. 3—How body and mudguards look after shaping




**T**HIS useful fitment can be proportioned to fit any size of kitchen cabinet, choosing the dimensions to suit the space available. Towels or drying cloths are hung on the dowel arms, the whole unit capable of being pulled out or pushed in, as required. Towels or cloths stored in this way air better and dry quicker, and with the door shut everything is out of sight.

Construction is simple. One or both 'door spaces' of the cabinet can be used. Two lengths of channel are built up, as shown, exactly to fit the length of the available space inside the cabinet.  $1\frac{1}{2}$  in. by  $\frac{1}{2}$  in. and  $\frac{3}{4}$  in. by  $\frac{1}{2}$  in. stock is used for this, screwed and glued together and also screwed in place. Use countersunk wood-screws throughout.

Into these two channels fit the dowel carriers. These are identical, cut from  $\frac{1}{2}$  in. material. The end is tongued to fit the grooves in the fixed channel sections with  $\frac{1}{8}$  in. clearance for smooth operation. From the bottom of each of these carriers mark off a line  $\frac{3}{4}$  in. and punch centre holes at approximately 2 in. spacing. Drill  $\frac{1}{2}$  in. to take

the dowels. The assembly of this unit is obvious from the diagram. The dowels should all be glued in place.

The length of the dowels must be arranged so that there is adequate clearance for the door to close with the rack fully closed. A spacing of about 7 in. between the two carriers provides a stable support. A suitable stop can be fitted at the extreme outer edge of each channel section to prevent the whole carrier being completely withdrawn. (371)



Showing construction of channels and dowel carriers



# Hints for the handyman-gardener on LAWNS AND THEIR MAKING

It generally falls to the lot of the home handyman to tend the household lawns, and now is the time when these attractive features of domestic life should receive attention.

If you do not possess a lawn but are desirous of making one, it is much better to prepare the ground and set seed than lay sods taken from elsewhere. Sodds seldom 'root' consistently, and it is difficult to get them to present a perfectly flat surface, for if the underlying ground is hard they will not catch on, while when it is soft the turfs sink, causing uneven depressions.

Before setting seed, the ground should be dug for about 1ft. in depth. Large lumps must be completely broken down and all stones and weeds removed. Sowing is best in showery weather, although with a hose the ground can be artificially moistened. Never attempt the sowing at very dry, windy times as grass seed is light and easily blows away. In any case, high wind makes even distribution—which is essential—almost impossible.

## Peg Out the Ground

About 1oz. to 2ozs. of seed must be used for every square yard of ground and it is really a good idea to peg the area out with strings to ensure that equal distribution is being obtained.




Fig. 3—Levelling a sloping lawn

To prevent ruining the prepared ground, perform the sowing standing on a plank to distribute your weight, and when the seed is down, cover only with the finest layer of soil, otherwise germination may not take place. Actually, grass seed need be no more than  $\frac{1}{4}$ in. below the surface and it will be found that this thin covering can be secured by raking gently in two opposing directions.

## Use a Light Roller

When the new shoots are about 1in. high, a very light roller can be used with advantage over the surface, but no cutting should be attempted till shoots are in the neighbourhood of 2ins. Up to this period the new lawn must be kept under continual observation, and weeds or coarse blades that may appear must be ruthlessly pulled out. Any stones that were missed in the first preparation should also be removed—in fact get rid of anything that looks as though it

might be going to cause an inequality in the final sward. All this can be done without causing damage to the ground if you always work from the weight-distributing plank.

## The Use of Turf

If for some special reason you are desirous of laying your new lawn with turves, the main thing is to get these as large as possible (little bits of grass are




Fig. 1—Levelling a new lawn

useless) and cut with perfectly straight edges so that each will sit tight up to its neighbour. A handy size of turf is 3ft. by 1ft.

Once laid, the area should be given a tamping with a wooden 'beater' of some considerable area. This will ensure everything being as flat as possible, but, as pointed out, a perfectly even surface with loose sods is not easy to obtain unless the condition of the new rect-

men do when laying a concrete surface. Two persons, if possible, should work the length, which is taken slowly forward from end to end of the area being prepared, pushing unwanted soil before it. With this straight-edge depressions are easily detected and can be filled up with surplus soil from other parts.

## Make Side Strips

For very accurate use of this method, two levelled-up side strips should be put down (as shown in Fig. 1) along




Fig. 2—The rotating plank method

which the ends of the plank can slide. It is good, too, to have a spirit level temporarily fixed to the top edge of the wood at the mid point for continual reference.

Some lawns, by the very nature of the land, have to slope, and then this plank method cannot be used in its entirety, but it is generally possible to get a horizontal line in one direction, and this should be aimed for.

Another way to get a level surface with a long plank is to put a strong pivot of wood in the centre, sink this in and then rotate the length as in Fig. 2, which gives a complete circle of flatness. When one circle is finished the plank is moved on to an overlapping area, and so on till the whole area is completely traversed—the holes made by the pivot being carefully filled.

## The Sloping Lawn

In the case of a sloping lawn that you wish to level, this can be effected (see Fig. 3) by working from a centre line, digging out the ground from the raised portion and carrying it forward to the depressed end—allowing for sinkage here.

Excessive moisture in a lawn is bad as it makes for heaviness and mud. Grass flourishes best in firm but porous, airy soil. Drainage can be effected in bad cases by using the standard agricultural drainpipe. These are bought in quite small sections 12ins. long by 3ins. diameter, and are laid 12ins. to 18ins. below the ground, and sloping at 1in. in every 10ft. to some point where the water coming into the pipe-line formed can readily drain away. It is no good having nowhere for the water to go.

Agricultural drain pipes are not




Fig. 4—Draining

angles and under-soil is ideal. Once laid, the turves should be kept freely watered until they root.

The laying of turves for a new lawn, although it is not the best method, has some advantages. The lawn is rough-finished from the start, and if you are able to get your own turves in the country instead of buying, it is not so costly as seed-setting.

In the preparation of any ground for lawn-making, the question of levelling is of the utmost importance, while drainage should not be overlooked. One of the best ways of levelling with loose soil is to use a long plank on edge, as road-

(Continued foot of page 404)



# Any youngster would be pleased to have this USEFUL PENCIL BOX




Fig. 1—The completed box

**T**HE pencil box indicated in Fig. 1, and the same box with cover removed in Fig. 2, is just the thing to make either for yourself, or for your young brother or sister. The box lid is provided with a piece of emery cloth on which the pencil can be sharpened, as indicated in Fig. 2.

Also a piece of blotting paper is fixed on the lid which is useful for cleaning the pen nib, or rubbing the pencil point over to clean off any powdered lead after sharpening on the emery cloth. The box is quite simple to make from good sound pieces of  $\frac{3}{8}$  in. plywood, and all the parts are fixed together with glue.

and this is easily done with a file and glasspaper.

## The Front

The front for the box is simply a piece of plywood cut  $7\frac{1}{2}$  ins. long by  $1\frac{1}{2}$  ins. wide, as indicated in (C) Fig. 3. The parts thus cut are well smoothed up with glasspaper, and then fixed together with glue and allowed to set hard, after which all surplus glue showing can be carefully scraped off.

## The Bottom

The bottom for the box is indicated in (D) Fig. 4, and simply consists of a piece of plywood cut carefully to size  $8\frac{1}{8}$  ins. by  $3\frac{1}{8}$  ins. Well smooth up the piece when cut, and glue it in position with an overlap of the edges  $\frac{1}{8}$  in. all round.

Details of the box lid top are given in (E) and (F) Fig. 4. Cut a piece of plywood




Fig. 2—The box with the lid off




Fig. 3—Details of the sides, back and front

Commence on the sides, details of which are given in (A) Fig. 3. Cut two pieces 3 ins. long by  $2\frac{1}{2}$  ins., tapering the top edge down to  $1\frac{1}{2}$  ins., as clearly indicated. Cut two pieces  $2\frac{1}{2}$  ins. by  $\frac{1}{2}$  in., and two pieces  $1\frac{1}{2}$  ins. by  $\frac{1}{2}$  in., and glue




Fig. 4—Dimensions for the top and bottom

$8\frac{1}{8}$  ins. by  $3\frac{1}{8}$  ins., as indicated in (E) Fig. 4, and the positions of the blotting paper and emery cloth are also indicated. The blotting paper and emery cloth are fixed by a little glue applied along the edges.

Next cut four pieces of plywood 1 in. by  $\frac{1}{2}$  in., and carefully glue them on the underside of the lid, in the positions shown in (F) Fig. 4. The edges of the pieces marked (X) in view (F) Fig. 4, are carefully filed until the lid fits nicely in position on the box top.

The box can now be finished off by applying a coat of stain. (376)

## Lawns and Their Making—(Continued from page 403)

cemented together, but merely laid end to end, and the trench in which they lie must be filled with light soil, not heavy impervious clay. With small lawns one pipe taken diagonally across with a branch to each corner will generally do all that is required (Fig. 4). Bigger lawns need more considered treatment.

Where a lawn is already in existence, the best way to get it into trim is by the consistent use of a good mowing machine—if possible with roller attached. Mounds can be removed by turning back the turf, digging out the unwanted soil and replacing the turf. Small hollows are best filled by continual

dusting with sand till the desired level is reached—the turf not being disturbed.

Worms are sometimes a real nuisance as they keep the ground too loose and throw up unsightly casts. The trouble can be well dealt with in Spring by the use of a worm killer, as February to the end of May is a breeding season. (402)



# Here is some helpful advice on BRICKLAYING FOR BEGINNERS

**T**HE building of a low wall is well within the scope of the average handyman provided his effort is guided along the right lines. Such a wall can be put to many uses, decorative and otherwise, especially in the garden.

## The First Step

Mark out the position of the wall and dig a trench 12ins. deep, 15ins. wide and, if possible, about 1ft. longer than the intended length of the wall. Ram the




Fig. 1—The foundation trench




Fig. 2—The foundation and first courses




Fig. 5—Pointing the joints




Fig. 6—Building up a corner

bottom of the trench until it is hard and firm. On to this will go a 4in. layer of concrete.

Along the middle of the trench drive in wooden pegs 3ft. apart, leaving 4ins. of each peg above the ground (Fig. 1). Put a piece of deal boarding across the first two pegs and test with a spirit level. In this way adjust the pegs all along the trench so that their tops are all perfectly level.

## Mixing the Concrete

A suitable mixture is:

- 1 bucketful of cement.
- 2 bucketfuls of clean sharp sand.
- 3 bucketfuls of gravel.

Use a wooden or stone base for the mixing. First tip the gravel into a heap. Over this put the sand and finally, the cement. The easiest way to do the mixing is to shovel the heap over into another heap and then shovel it back again. Keep this up until the mixing is complete.

Now sprinkle with water from a watering can and repeat the mixing process until there are no dry 'pockets' of material left in the heap.

Tip the cement mixture into the

trench and use a piece of boarding to level it off flush with the tops of the wooden pegs.

## Making Cement Mortar for the Wall

Cement mortar is preferable to lime mortar in that it is easier to mix and cleaner to use.

The mixture:

- 1 part cement.
- 5 parts clean sharp sand.

Mix in the same way as for the foundation concrete until the whole mass is the consistency of cream.

## Laying the Foundation Course

The foundation course is the layer of bricks placed immediately on to the concrete base. In this particular case the course is one brick wide and one brick high. Spread a ½in. thickness of mortar on the concrete base and on this lay the bricks crossways to the run of the wall



Fig. 3—Essential arrangement



Fig. 4—Ends of wall built first




Fig. 7—How courses are built up when strengthening a wall with piers

(Fig. 2). Such bricks are called 'headers'. Those running in the same direction as the length of the wall are called 'stretchers'.

Use a

straight edge and spirit level to level up the foundation course and, where necessary, use the handle of the trowel to tap the bricks into place. Now test the face of the bricks with the straight edge so that the whole course is squared up.

## The Wall Itself

Fig. 3 shows the essential arrangement; each brick overlaps the joint immediately above and below it. This overlapping is a 'stretching bond' or a 'chimney bond'.

To do this start all odd numbered courses with a whole brick and all even numbered courses with a half-brick.

The layer of mortar between each course, and the dab of mortar at the end

of each brick should be a ½in. thick. Wet the bricks beforehand to make a strong union. Firstly build the ends of the wall up to six courses, and then work to the middle of the wall (Fig. 4).

## Cutting Bricks in Half

To cut a brick in half use a broad chisel called a bolster. Scratch the brick on each side. Place the chisel on the scratch on each side in turn and give it a blow with a hammer. A heavy blow with the hammer will now break the brick in half. These half bricks are called brickbats.

## Building Up the Wall

Fasten a length of string to two nails, or better still, use proper bricklayer's 'pins'. Push the nails into a mortar joint so that the line is taut and at the level of the first course (Fig. 4). This course is now completed and the line moved up to

the level of the next one.

When the sixth course has been completed start on the ends again. Build them up to the required height (ten to twelve courses) and then build up the middle portion again.

## Pointing the Joints

Where the face of a wall is exposed to the weather it must be treated so that water cannot lodge in the joints.

Put the trowel flat against the top of a joint, pressing the mortar in at the top and flush with the brick at the bottom. Fig. 5 shows the final effect.

Where a face is not so exposed the joints are given a flush finish. The mortar is pressed tightly into the joint and the surplus scraped off level with the bricks.

This type of wall can be used for the building of a coal-bunker and so on. Fig. 6 clearly shows how the corners are made.




Fig. 8—A completed pier



## Building a Higher Wall

If this type of half-brick wall is to be built higher than ten to twelve courses, it must be strengthened by means of piers built at regular intervals along its length.

This time the base is made of a 6in. depth of concrete and the trench must be

widened wherever a pier is to be built. Fig. 7 shows the arrangement of the bricks for the foundation courses and for the odd and even numbered courses. The completed pier is shown in Fig. 8.

## The 9in. Wall

Dig the trench 30ins. wide and lay a

### The Nine-Inch Wall

Perspective View  
of courses




Fig. 9—Foundation course

Plan of courses





Fig. 10—Second foundation course




Fig. 11—First course



Fig. 12—Second course



6in. layer of concrete.

First foundation course—two bricks wide (Fig. 9).

Second foundation course—a brick and a half wide (Fig. 10).

First course and all odd numbers—Fig. 11.

The shaded brick is only 2½ins. wide and is called a 'closer'. The closers are used to make the headers fall across the joints between the stretchers.

Second course and all even numbers—Fig. 12.

The finished wall is illustrated in Fig. 13.

## The Plumb Rule

The plumb rule is used to make sure that the ends and the face of the wall are vertical.

The easiest way is to hold the rule against the bricks with the left foot and left hand. With the trowel handle tap in protruding bricks until the metal bob hangs exactly in the centre of the hole and the cord lies just in front of the groove. (382)




Fig. 13—The finished wall

# The Work of a Craftsman

**F**ROM Mr. T. Smith, of 7 Station Avenue, Eastfield Estate, Bolton (Lancs.) comes this picture of 24 of the models he has made during the past few years—mostly from Hobbies patterns.

Among them we notice a model of St. Paul's, The Coronation Chair, the ½d. Galleon, the Santa Maria, two locos—the Gt. Northern Pacific type nearest camera, and the old-timer 'North Star' on the left—a stage coach, and numerous of our fretwork designs.

Mr. Smith has certainly been busy, but he has something to show for his labours. And something to be proud of, too, for, as far as we can see from the photograph, the models are extremely well made.





# You should find it easy to make this BEDSIDE LAMP AND CLOCK

**A** CLOCK in the bedroom is really only partly fulfilling its purpose if there is no light in a handy position for seeing it. It is generally during the dark hours that we want to refer to it and then a light of some sort is essential.

The subject of this article is a combined bedside reading lamp and clock that fulfils these requirements. It is quite an attractive piece of furniture designed on modern lines and should find a ready appeal.

The switch mounted on the baseboard in front of the clock makes operation quite simple. It is well within reach when lying in bed and the clock is adjustable to any angle.

The lamp has been designed to work off the mains but it could be easily adapted for use with batteries if desired.

## Which Wood

The choice of wood is rather important, and a hardwood such as oak or walnut is to be preferred. Even if the woodwork is to be painted with one of the modern lacquer finishes a hardwood should be used if possible.

Three separate pieces of wood make up the base and have a total thickness of 1 in. The top one, which is 8 ins. long, 5 ins. wide and  $\frac{1}{2}$  in. thick could be made of plywood but a solid piece of wood would look better. For the middle section cut a piece 8  $\frac{1}{2}$  ins. long, 5  $\frac{1}{2}$  ins. wide and  $\frac{1}{2}$  in. thick, and this could be cut with the grain across the width to give variation to the design. This centre section has a 4 in. square hole cut in the centre to allow room for the switch and all the necessary wiring.

Cut a piece of  $\frac{1}{2}$  in. thick wood 9 ins. long and 6 ins. wide for the third section which is screwed in position when the wiring has been connected up.

Next cut the two supporting bars from wood 1 in. square. Allowing for the piece let into the baseboard  $\frac{1}{2}$  in. and into the top bar  $\frac{1}{2}$  in., the total length will be 6  $\frac{1}{2}$  ins. Cut two square holes right through the top two sections of the baseboard to just fit these supports—there must be a clear space of 5 ins. between them.

One of the supporting bars is hollowed out for the wiring to pass down, and the best way of doing this is to use two pieces of  $\frac{1}{2}$  in. wood for this side instead of one square piece. Cut the grooves large enough to take twin flex and then glue together.

## The Clock Panel

Before we can fix the supports into position the clock panel must be made. It consists of a piece of wood 5 ins. long, 4 ins. wide and  $\frac{1}{2}$  in. thick, and in the centre a hole is cut of sufficient size to fit the clock. No definite information can be given regarding this, as it entirely

depends on the clock used and must be left to the reader's discretion.


This bedside combination was designed to take the popular little time-piece now made with dials of such diverse shapes and sizes. The movement behind the dial is contained in a drum having a diameter of about 2  $\frac{1}{2}$  ins. and this is the size to be cut out of the panel. A fairly tight fit is usually sufficient to hold the clock in position, but you must use your own discretion regarding the fixing.

It may be that you already possess a clock mounted in a wood panel that can be cut to the necessary size to fit between the supporting bars. Another idea is for the clock panel to have a slight sink cut in the centre to fit a pocket watch, which is suspended on a neat little hook.

Two pivots must now be fitted to the clock panel in order to make it adjustable to any angle. In the centre of each end drill a hole about  $\frac{1}{2}$  in. deep to take a length of  $\frac{1}{2}$  in. dowel rod. Make it a fairly tight fit and glue in position, leaving a piece projecting about  $\frac{1}{2}$  in.

The two supports have holes drilled to receive these dowel pivots 2  $\frac{1}{2}$  ins. up from the baseboard. Make them a movable fit, but at the same time they must be fairly tight, or the clock may swing over by itself.

Now is the time to fit the clock panel into the supports and then glue these firmly into the baseboard. At the same



time the two top sections of the baseboard can be glued together.

## The Top Bar

The curved top bar which supports the electric light holder can now be cut and fitted to the side bars. Like one of the side bars it is best made in two halves, so that a groove may be cut to take the flex from the holder.

A piece of wood 8 ins. long, 3 ins. wide and  $\frac{1}{2}$  in. thick will cut one side, then lay it on another piece of wood and cut a similar piece. Cut a mortise in each end to fit the tenons on the side supports before cutting out the grooves for the wires. Quite shallow grooves will be sufficient to take the flex, and this must be placed in position before fastening the two halves together with glue.


Cut a block of wood 2 ins. diameter and  $\frac{1}{2}$  in. thick and glue to the centre of the top to screw the lamp holder on to. Drill a  $\frac{1}{2}$  in. hole in the centre for the wires to come through.

Before the final finishing, mark and cut the hole for the switch. A small tumbler switch of the wireless type capable of carrying a current of 3 amps. will do nicely.

Glasspaper all quite smooth and finish either with french polish or one of the modern lacquers chosen to match the existing furnishings.

Take a little time and care over wiring up and leave no loose strands of flex when connecting to the holder and switch, especially if you are going to work off the mains.

(Continued foot of page 410)



General dimensions



# An interesting hobby FOR CYCLIST AND HIKER

**W**HEN out cycling or hiking there is no more interesting side hobby—if you have a bent in that direction—than the making up of a naturalist's book of specimens. The pastime need not be very arduous, but the collector's satisfaction in getting a new leaf here or a good specimen there is great—so why not give it a try?

The big book in which you keep your collection will, of course, be left at home, but something in which to store the specimens temporarily must be taken with you on the run. Flowers and leaves wither quickly if carried in the hand or if they are exposed for too long periods to a hot sun or drying wind, so the 'something' must be efficient.

## A Container

A tin box with a tight-fitting lid and some damp moss in is quite serviceable, or an old book can be used, placing the items between the pages. The latter is all right for leaves, but not very satisfactory for bulky flowers, etc. which, apart from anything else, require care in pressing and which may be spoilt by the first incorrect pressure. In these cases a box is better—and this can be quite shallow, and need not take up too much room.

For a general plant collection the best specimens are those which exhibit a leaf and flower together, and the ideal time to collect is just before the flower is full out. Back home, if you have not time to deal with the specimens at once, it is best to put them in water.

The pressing of a specimen needs some little care if it is to be done properly. It is, of course, the squeezing of all the moisture and sap from the stems and petals without destroying the outlines.

Good pressing can only be done fairly slowly. Trying to rush the job only ruins things. Required is some good stiff cartridge paper (which can now be obtained again). The specimens are taken from the water and drained, and the first one laid on the first sheet of paper. Carefully arrange how you want the petals and parts to go and then place another sheet of paper on top. On this sheet can be adjusted a second



COMPLETED  
ALBUM



Details of the album

specimen. When several layers have thus been made up, place the block on some firm surface where it will not be interfered with, place a board on top, and a weight on this.

Examined after a day, it will be found that only partial pressing has taken place. Carefully remove the specimens, dry out the cartridge papers and restack with a slightly heavier weight. This process may have to be repeated a number of times (according to the type of specimens) before full pressing and drying has taken place.

## Mounting

When ready, the specimens must be

mounted in the album that is to be their permanent home. At one time, 'news-paper cutting' books could be obtained fairly cheaply, and made excellent albums for botanical specimens, but now it is best to make your own book, and no handyman will find this difficult.

## Making an Album

Cut several sheets of strong paper of medium wrapping-paper thickness and some pleasing colour. Such papers can be obtained now at most stationers or printers. The size should be about 12ins. by 8ins. At the same time, cut two rectangles of card the same size for the cover and back.

At about 1½ins. in from the end of each card, score a line with the tip of something blunt, so that the card will bend here without cracking. Now punch three holes in the flap so formed, and also a single hole at the other end to take a fastening tape.

The leaves now are given holes at the ends corresponding with those in the cards, and the album is made up by putting the leaves between the cards and lacing up with a leather or other boot lace. At the further end two tabs are put on and these are tied together in an easily released bow when the book is closed. An album made thus is really loose-leaved and can be built up to almost any size.

## Holding the Specimens

Adhesive paper is the best thing to use for holding the specimens in position and below each should go a neat strip of paper bearing the name. Once pressed and dried, handle specimens only by tweezers or by sliding a thin knife underneath them. (401)

# Realism in Model Work

**T**HE writer has just been examining some very well made ship models, ancient and modern, and without wishing to be unkind, cannot help remarking that even the model trawlers appear to have golden chains, silver metalwork, and maple dance hall floors for decks.

When shipping lines commission a model they like to have the newness of their ship emphasised. In the case of a model trawler, however, the model-maker would do well to paint on some realistic red rust, etc. and begrime the funnels.

The same applies to models of all descriptions. For example, the underside of a concrete railway tunnel is always black from the smoke of trains. In any length of fencing, it will add to the

realism of your model if one or two of the posts or rails are shown broken or otherwise out of place. In model houses where a lot of windows are shown, it will look more natural if appropriate ones are shown cracked, broken, patched or boarded up. In real life many rain gutters are kinked. Again, if one is to include a road in a model, a study of the real thing will soon show that the surface of the road is often marked by patches of oil from standing cars, etc. Sufficient has been shown to emphasise my point.

Old-time ship models should be treated to look antique, in other words, to look as if they were contemporary models. Tins of 'antique' medium are sold, but for a few pence the writer could make far more antique medium than he could ever possibly hope to use

in a double life-time. All that is necessary is a little soot from the chimney (only a little!) mixed with paste (either ordinary flour and water paste, or the proprietary makes). This stuff is dabbed on the model with an old brush, working it well in the crevices. After a minute, it is wiped off again with two or three changes of rag.

It is as well to practice on a spare piece of wood first, and, in any case, do not attempt to cover the whole of the ship at once. One should attempt to wipe off in the same way as decorators 'grain' varnished doors, etc. The effect should be of age, not of dirt. As a matter of fact, it is the soot in the air that gradually deposits upon a genuine old model and gives it an antique effect, so this mixture of soot and paste closely approximates Nature's own way. (102)



# There will be satisfaction in making this STURDY GARDEN SEAT




Fig. 1—The completed seat

**A** GOOD garden seat is almost a necessity to a garden and lawn of any reasonable size. The seat shown in Fig. 1 is so constructed that the back rest is adjustable, being pivoted to a lower side rail so that it can be swung back to suit the direction of the sun. Thus, the full benefit of the sunshine can be felt regardless of what position the seat takes on lawn or garden.

The seat shown in our illustration can be made from white wood. A good straight-grained deal, finished with paint, or even creosote, would make quite a

serviceable job and, be of attractive appearance.

The constructional work is simple, comprising nothing more than a few simple mortise and tenon joints. These joints, however, need to be carefully set out before the work of chiselling is proceeded with, and here again a set of good tools is needed if clean joints are to be made. All the joints so made should be securely dowelled to make them more resistant to weather conditions.

## The End Frames

The two end frames of the seat should be made first, and for these you require four pieces of 2½ in. square wood 17 ins. long for the legs. For the bottom rails, two pieces 20 ins. long by 2½ ins. by 1½ ins. are required, and for the top rails two pieces 20 ins. long by 3 ins. by 1½ ins. are needed. These latter rails are slightly hollowed towards their middle, as shown in Fig. 2, to make the




Fig. 2.




Fig. 4

seat comfortable. This shaping, however, is not compulsory, as cushions are frequently used for such a hard seat.

The joints can now be marked out, and it will be noticed that the tenons on the top rails are on one edge of the wood and extend to half their thickness. The tenons on the bottom rails are one-third the thickness of the wood, and the ends are mitred so that the two tenons

fit together in the mortises which meet in the legs (see enlarged details at Fig. 3).

Mark out the mortises on the legs to correspond with their respective tenons. It will be noticed from Fig. 3 that the upper mortises are made open at the top, these joints being hidden and sufficiently covered by the seating boards, as Fig. 2 shows. In this diagram is shown, too, the lengths between the shoulders on the rails. The joints can now be cut out very carefully with the tenon saw, and mallet and chisel for the mortises. Most of the wood in the latter can be cleaned out by using a brace and bit of the required size and using the chisel for clearing away.

It is advisable to trim out the mortises on the other sides of the legs, which receive the front rails, at the same time. These are exactly the same in size and shape as the others.

The next job is to fit the frames together. With a ¼ in. twist bit bore two holes through each joint for the dowels, which may consist of ¼ in. round rod pointed at the end and smeared with a mixture of glue and paint to resist the weather.

Cut the ends of the dowels off flush with the frame and clean up with the plane.

## Front and Back Rails

Two top and two bottom rails are now required to fit between the legs along the front and back of the seat.

The top rails are each 3 ft. 11 ins. by 3 ins. by 1½ ins., and the lower rails 3 ft. 11 ins. by 2½ ins. by 1½ ins. The tenons can then be marked out on the ends of these rails similar in size and shape to those on the end rails, the distance between the shoulders this time being 3 ft. 7 ins. The lower rail tenons must be mitred as before to fit in the mortises.

When all the joints have been cut and fitted, the tenons can be painted and the dowels driven through the legs into them as explained before.

The next job is to fix the top slats on the assembled frame. For these obtain two pieces of wood 4 ft. 3½ ins. long by 3½ ins. by 1 in. for the outside slats (see Fig. 2) and six pieces, each 4 ft. by 2 ins. by 1 in., for the intermediate ones. One edge of each outside slat must be rounded with a smoothing plane, and it is advisable to glasspaper the corners off the remaining slats to remove any splinters, etc.

The best way to fix the slats to the frame is shown in Fig. 6. A hole is bored through the wood where the screws are to go and the tops are then counter-sunk deeply. The screws are then




Fig. 3



Fig. 5



Fig. 6

(Continued at foot of page 411)



# Books to Read!

A review of interesting books for craftsmen which have been recently published. Obtainable through newsagents or book-sellers or direct from the publishers mentioned.

## Concrete, Stone & Brickwork

by Noel D. Green

THE home handyman who wishes to undertake successfully a variety of outdoor constructional work in concrete, stone or brick, should secure a copy of this latest addition to the Home Mechanic Series. Introductory chapters explain the various types of concrete mixes and the methods of mixing, and simple instructions are given for the types of work that can make so much difference to a garden—laying crazy paving, constructing garden edging, paths, balustrade columns, bird baths and aquariums. Chapters for the more ambitious worker are also included, and give practical instruction for the construction of reinforced structures such as fences, coal bunkers, garages and greenhouses. Masonry and brickwork are thoroughly dealt with in the final chapters.

Published by Newnes and Pearson Ltd., Southampton Street, Strand, London, W.C.2—Price 5/-

## Your Children's Crafts

Edited by E. Sheila MacEwan

THERE are many books on children's crafts, but this is one with a difference. It is planned throughout for children old enough to read instructions and follow simple diagrams for themselves, and avoids, as far as possible, the manner of the school textbook. Then again, it is not just another book on how to make something useful. The crafts—hand and glove puppets, modelling and carving, paper model making, print making, wooden toy making and weaving—are described rather as a media of artistic expression, and to encourage children to use, in an imaginative way, odds and ends of materials ready to hand.

Published by The Sylvan Press Ltd., 24 Museum Street, London, W.C.1—Price 9/6

## Make Your Own 'O' Gauge Motor

by E. F. Carter

THERE can be few railway modellers who have not read something from the pen of Mr. Carter, and few who have not profited from such reading. This latest book will prove a valuable asset to those of our readers who own 'O' gauge layouts, for are not numbers of us often deterred from constructing another

locomotive body, simply because we cannot afford to buy the motor it will need before it can take its place among the rest of our locos? By following the instructions in the book, a sturdy and reliable unit can be made for a fraction of the cost of a manufactured one, and for the man who contemplates putting a new loco on his layout, the book will be a profitable investment. For anyone faced with the problem of completing a number of locos to build up his stock, the book is indispensable.

Published by Percival Marshall & Co. Ltd., 23 Gt. Queen Street, London, W.C.2—Price 3/6

## Pewter Relief Modelling

By Zita Dundas

FOR anyone wishing to acquaint themselves with the craft of relief modelling in pewter, Miss Dundas' book can be recommended. Pewter work in a general sense is, of course, a highly specialised craft calling for skilled technical training, but pewter relief work in itself is a handicraft which requires few tools and can be practised by anyone. The book is easy to understand and well illustrated, and the illustrations include a number of designs which should offer no difficulty to the beginner.

Published by Vawser & Wiles (London) Ltd., 356/358 Kilburn Road, London, N.W.6—Price 2/6

## Home Carpentry

By W. A. G. Bradman

HERE is a book for the amateur woodworker, a book which sets out to provide a concise instruction course of real worth to the beginner. The chapters deal with such things as the tool kit, woodwork joints (explained stage-by-stage in text and pictures), fittings, cabinet drawers and doors, veneering, and staining and polishing. In addition, there is a section on six things to make.

Published by W. & G. Foyle Ltd., 119/125 Charing Cross Road, London, W.C.2—Price 2/6

## Rope Splicing

By P. W. Blandford

IN this book an attempt has been made to gather descriptions of all kinds of rope splices into one volume—

and a very handy volume it thus turns out to be. For while there are many excellent books on knotting and general ropework, and which include splicing in their contents, they cannot hope to treat the subject as fully as one devoted solely to splicing. So that the reader who wants to know about this particular subject alone cannot do better than secure a copy of Mr. Blandford's book. It is comprehensively illustrated, and altogether good value for money.

Published by Brown, Son & Ferguson Ltd., 52/58 Darnley Street, Glasgow—Price 3/6

## Modern Furniture Projects

By W. A. G. Bradman

FOR the amateur woodworker who is setting up home, or who needs additional pieces, this is a book that can be wholeheartedly recommended. It is assumed, of course, that the reader has the essential pieces, and the articles concentrated upon are, for the most part, of the smaller variety such as stools, lounge tables, etc.; but larger pieces are not altogether neglected, and there are drawings and instructions for making divans, a sideboard, etc. A chapter on joints caters specially for the reader of limited woodworking experience, and he need not fear that the subsequent designs will be too difficult for him. The designs themselves are modern, pleasing to look at—and useful.

Published by Herbert Jenkins Ltd., 3 Duke of York Street, London, S.W.1—Price 7/6

## Aeromodeller Annual 1950

Compiled by D. J. Laidlaw-Dixon;

edited by D. A. Russell, M.I.Mech.E.

ONCE again comes this now old friend to mark the passing of another aeromodelling year. It gives, as usual, a detailed review of the year's aeromodelling throughout the world in theory and practice, and is full of useful data and authoritative articles produced by the staff and contributors of the Aeromodeller. The popular plans section has been not only retained, but enlarged, and several new countries are represented. In all, the annual offers sound value for money to all who make and fly model aircraft.

Published by the Model Aeronautical Press Ltd., Allen House, Newark Street, Leicester—Price 7/6

## Bedside Lamp and Clock—(Continued from page 407)

Leave a sufficient length of flex to connect to the source of supply; about 2yds. is usually enough but this will depend on individual requirements.

The bottom board can now be fixed on with a few 3in. screws, and if desired a piece of thin felt can be glued on to prevent scratching the furniture.

Choice of shade is left to the reader; there is an endless variety on the market now, or it is not a difficult job to make one. (388)



# Good news for amateur photographers— 'P.O.P.' IS HERE AGAIN

**'PRINTING-OUT'** photographic paper, generally called P.O.P., is back on the market after its long absence due to the war. This is excellent news for the amateur camera man, for making prints with this kind of paper is very easy, no darkened or semi-darkened room being necessary as with bromide or gaslight papers. Also, when watching a P.O.P. print come into being there is an interest that seems absent with other developing papers.

With the daylight paper, the negative is placed in the frame with a sheet of the material behind, exposure to daylight then being made. The frame must not be placed in the full sun, and the making of the print is quite a leisurely job. After the frame has been out for a little time take it into the greater shade of, say, a doorway, undo half the back and gently lift the paper from the negative. At once you will see that the picture has arrived, though as yet it may not be dark enough.

## The Correct Depth

The picture has, of course, been produced by the action of the sunlight through the negative and the longer it is left in the light the darker it will go. The correct depth to aim at is just a little deeper than you require the final picture to be, as the print will lighten in the 'fixer', some brands more than others.

Although there is an almost irresistible urge to get a really good long peep at your latest snapshot, do not keep the half back up for too long, as the light in the doorway may be brighter than you had imagined and the paper will start to darken all over, which will spoil the sheet. After just a very brief look, therefore, close the half back down carefully, re-clip and, if necessary, place the frame back in the sun. With a little practice you will be able to get the desired depth of printing without too

many inspections.

Having completed the printing, remove the sheet and put it in the envelope in which the paper arrived (and which is quite light-tight) till you are ready to do the fixing. The usual thing is to print quite a number of negatives and then fix the prints altogether. However, try with single prints at first until you get your hand in.

## The Two Types

Printing-out papers all give a brown picture and there are two types of the material, the 'ordinary' and 'self-toning'. Both are 'fixed' by placing in hypo, but whereas the 'self-toning' turns to a rich sepia in plain hypo, the 'ordinary' has to be placed first in a 'toning bath' to get the same effect. Treatment with hypo will certainly fix the ordinary papers without the toning solution, but the final colour is not too nice, being reddish and devoid of the rich depth of true sepia.

If there are special instructions necessary for the using of any particular brand of P.O.P. these are usually enclosed in the packet, but generally the prints are first rinsed in plain water for a few minutes and put straight into hypo which has been made up to a strength of roughly 1oz. of the hypo crystals to 10ozs. of water. In here the prints slowly change to a deeper and deeper sepia, at the same time slightly lightening. Ten minutes in this bath is sufficient, and then the prints are washed for half-an-hour in running water. That the water must be running over the prints is important.

The 'ordinary' type of paper is first rinsed and then placed in the 'toner' which can be bought in small packets from any dealer. The prints stay here for about 5 minutes, being kept on the move and in a shady place, and are then put in a hypo solution as before.

Printing-out papers can be dried

naturally by laying out on clear blotting paper, but the glossy types 'glaze' exceptionally well; that is, they can be given a super high gloss by placing face down on a sheet of glass when wet. The prints are taken straight from the washing water and put quickly on to the glass. A piece of clean blotting paper is then placed over their backs and they are pressed into tight contact with the smooth surface, either with a squeegee roller or by pulling some flat edge (e.g. a ruler) over the blotting paper which is firmly held meanwhile so that the prints do not slip. The aim is to expel all air from between the print and glass.

The glass is now put on one side, and as the prints dry they peel off with a depth of gloss that is quite impossible by straight drying. Should they stick at all it is because the glass has not been absolutely clean. Stuck prints, however, can be soaked off, and reglazed when the glass has been given another polish. French chalk makes an excellent grease-removing and polishing agent.

## Unfixed Prints

P.O.P. is useful also to the photographer who mainly uses gaslight or other developing papers, as it allows him to see in a few moments what he has really got on his negative. In fact, some years ago it was much used by professional photographers for 'proofs'. While unfixed P.O.P. prints cannot be looked at for too long in daylight without browning in, they can be examined for any length of time by artificial light without damage.

One final point. The best P.O.P. prints are obtained from fairly strong, contrasty negatives, and these can be obtained by developing the film for a rather longer time than usual. A little experimenting will soon show you the best class of negative for this extremely handy paper. (400)

## Sturdy Garden Seat—(Continued from page 409)

driven in and the heads filled with putty or other suitable filling. This covering prevents the screws from rusting. Two screws driven in each end of each slat is sufficient if a piece of odd wood is screwed across the middle of the slats on the underneath side to make everything rigid. Screw the two outside slats on first, and notice in Fig. 4 that they are  $1\frac{1}{2}$  ins. longer than the seat at each end—to receive the back rest. The intermediate slats must also be longer than the top rails of the seat frame, but level with the edges of the legs. These slats are spaced out carefully between the front and rear wide slats.

## Making the Back Rest

For the back rest, obtain two side uprights about 3ft. 3ins. long by 3ins. by

$1\frac{1}{2}$  ins., and two horizontal rails 4ft. 3ins. by  $1\frac{1}{2}$  ins. Mark out the mortise and tenon joints as shown in Fig. 5. The tenons are  $\frac{1}{3}$ rd the thickness of the rail and pass right through the uprights. Cut these and fix them as before, by gluing and painting and then dowelling. It is better to round the ends of the uprights and plane all the corners off before fixing together as above. Next obtain two 4ins. by  $\frac{1}{2}$  in. bolts, with nuts and washers complete, then put the back rest in position so that the bottom of the uprights fit the lower rails of the frames as in Fig. 2. First, however, bore holes centrally in the rails to receive the bolts. The back rest should move freely against the slats of the seat. Any clearance needed can be arranged by adding washers on the bolts.

The completed seat may be oiled, painted or creosoted, the bottom of the legs being coated with tar, or thoroughly saturated with the creosote.

## HOBBIES BRANCHES

LONDON, 78a New Oxford St., W.C.1  
87 Old Broad Street, E.C.2  
117 Walworth Road, S.E.17  
GLASGOW, 326 Argyle Street  
MANCHESTER, 10 Piccadilly  
BIRMINGHAM, 14 Bull Ring  
SHEFFIELD, 4 St. Paul's Parade  
LEEDS, 10 Queen Victoria Street  
HULL, 10 Paragon Square  
SOUTHAMPTON, 25 Bernard Street  
BRISTOL, 30 Narrow Wine Street





## MARCH MEMORIES

It would appear that the merry month of March is an important one for philatelic commemoratives, either births or deaths. If we go through the diary we find that on March 3rd Alexander Graham Bell was born. You can see his portrait on either the 10c. of the United States set of famous inventors issued in 1940 or else on the 4c. Canadian stamp which was issued in 1947 to commemorate the centenary of his birth in 1847 in Edinburgh. He went to Canada from Scotland when he was twenty-three. He became professor of vocal physiology at Boston University and specialized in teaching the deaf and making aids for those who had difficulty in hearing, and it was from his researches into this that he developed his idea for a telephone which he invented in 1876. It is for this invention that we mainly remember him. He died in 1922.

On March 6th, 1945, Cologne was captured. We do not suggest that this is a birthday, of course, but it is quite a

1938, which shows Masaryk holding up a small child in a very happy mood.

On March 12th, 1925, Sun Yat Sen died in Peking, he was born in 1867 and was the founder and first President of the Chinese Republic as well as the first graduate in medicine at Hong Kong in 1892. He played a large part in the revolution of 1911, and the next year he was elected President of the Southern Provinces, but soon resigned. His portrait first appears on the 1912 set. Then he appears on the stamps of 1931 and 1938 and then each succeeding year from 1941, so that you should not have any difficulty in finding a good picture.

### Karl Marx

On March 14th, 1883, Karl Marx died and was buried in London. He was born in Prussia and went to the University, where he became the editor of a paper which was suppressed. This was in 1843, the same year in which he was married and went to Paris where he did much work on Socialism. Later, he founded

commemorated on the stamps of Norway by a set of four issued in 1928 showing his portrait and also his signature.


### The 'G's

The last three of the month's commemoratives are all 'G's—Goethe, Goya and the Duke of Gloucester. Goethe died in 1832, and his portrait appears on the two values 3 pf. and 25 pf. of the 1926 issue of famous Germans. Born in 1749, Johann Wolfgang Goethe studied at Leipzig and at Strassburg, and many of the plays he wrote met with immediate success. His most noted, 'Faust', was published in 1831. He was a scientist of no mean standing but this is completely overshadowed by his fame as a writer.

Goya was born on March 30th, 1746, and studied art for a time at Saragossa. He later went to Madrid, and at the age of 19 he was travelling with a troupe of bullfighters into Italy. There he again took up art and later became the Court painter in Spain. As could be expected from his intimate knowledge of bull



Canadian 4c. stamp showing portrait of Alexander Graham Bell



Russian stamp with picture of Karl Marx and his grave in Highgate cemetery



Goya pictured on a Spanish stamp



Portraits of The Duke and Duchess of Gloucester on an Australian 2½d. stamp issued in 1945

notable date, and Cologne Cathedral appears on the 1923 German stamp of 10,000 mark value. The cathedral is the most noted building in the city, but we must not forget that it is also an important manufacturing town, cotton and woollen goods, scent, machinery, and chemicals being the chief products. It was the headquarters of the British Army of Occupation from 1918 to 1926.

### Masaryk

Thomas Masaryk was born on March 7th, 1850, and his portrait appears on many of the Czechoslovakian stamps. He founded the progressive Czech Party in 1889, and strongly opposed the pro-German influence in Austria, so that he had to leave his country when the 1914 war broke out. But after the war he became the first President of Czechoslovakia. Many and varied are his portraits, the most pleasing being, undoubtedly, the child welfare stamp of

the Communist League and in 1848 issued the Communist Manifesto. He was banished from Germany and came to London, where he lived in great poverty. The 50th anniversary of his death was commemorated by Russia in 1933. She issued three stamps, showing respectively: a view of Treves, his birth place, on the lowest value, with a small medallion portrait of Marx; a picture of Karl Marx's grave in Highgate cemetery (middle value); a portrait of Karl Marx (highest value).

The 20th of the month is the anniversary of the birth of Henrik Ibsen, who was born in 1828. He was a Norwegian playwright and poet whose works can be divided into three groups—first, historical dramas, mostly in verse; secondly, poetical fantastic plays of which 'Peer Gynt' is probably the best known; and thirdly, satirical dramas written in prose dealing with social conduct. He died in 1906, and is

fighting, his etchings on this subject were masterly. His portrait and three of his paintings appear on the 1930 set from Spain. He died in 1828, aged 82.

March 31st is the birthday of the Duke of Gloucester, who was born in 1900, the third son of H.M. King George V. In 1935, he married Lady Alice Montague Scott, his portrait, together with that of the Duchess, is on the 1945 issue of Australia during the time that he was Governor-General.

Newfoundland has always been noted for the portrait stamps that she has produced, and on the 1911 set the Duke of Gloucester appears on the 6c. stamp.

(399)

### FAKE PHOTOGRAPHY

To make a 'moonlight' scene, under-expose a negative of a daylight view and then overprint.



# MISCELLANEOUS ADVERTISEMENTS

**BE** Taller. Quickly! Safely! Privately! No Bappliance—no tablets—no dieting. Details, 6d. stamp.—Malcolm Ross, Height Specialist, BCM/HYTE, London, W.C.1.

**MODELS.** You can make lasting stone-hard models with Sankey's Pyrama Plastic Cement. Supplied in tins by Ironmongers, Hardwaremen and Builders' Merchants. Ask for instruction leaflet.

**TRANSFERS** for decorating toys, trays, furniture, fancy goods. List and samples, 3d. Flowers, pixies, dogs, nursery rhymes.—H. Axon Harrison, Jersey.

**LEARN** Shorthand by April 28th (1 hour's study nightly), 1st lesson, 2½d. stamp.—Duttons (Dept. HB), 92 Gt. Russell St., London, W.C.1.

**RUBBER** Tyred Metal Disc Wheels finished in red, green or blue enamel. 2ins., 2½; 3ins., 3½; per set of four. Post paid. Other sizes available up to 9ins.—The Joyden Toy Co., 193 Chase Side, London, N.14.

**DOLL'S** House fittings and papers; send S.A.E. for list. Doll's house plan special; send 2/6. Trade supplied.—Zimplan, 88 Ware Road, Hodderson.

**LORRY** Kits, 4 mm. and 7 mm. scale. Also large range of spare parts from which to build to your own design. Send for fully illustrated catalogue, price 1/—Wilson's Lories Ltd., 6 Gt. Winchester Street, London, E.C.2.

**BLUSHING**, shyness, nerves, self-consciousness, fears, ended. Details under plain cover, 1d.—Stebbing Treatment, 28 (HB) Dean Road, London, N.W.2.

**WHEELS** for Toys, and other accessories. Full lists will be sent on application to—The Joyden Toy Co., 193 Chase Side, London, N.14.

**100,000** Government surplus bargains. Gear units, containing numerous useful gear wheels, 2/6, post 6d.; indicator lights (red) for standard screw bulbs, 6d., post 3d.; ammeters, moving iron, 0-25 amps., 5/-, post 6d.; special sample parcel of assorted switches, junction and fuse boxes, resistances, etc., packed in useful wooden box, 6/6, including post. Send 3d. stamp for full list of other bargains.—Milligan's, 24 Harford Street, Brownlow Hill, Liverpool.

**PLYWOOD** Offcuts. Birch and Gaboon in various thicknesses. Handy sized parcels for the cabinet, toy, model maker, and all handicrafts. Parcels made up in £1 and 10/- lots. Carriage paid. Send P.O. to Reeves, Plywood and Timber Merchant, 33 Front Street, Monksheaton, Whitley Bay. Tel. W.B. 4677. Parcels are now despatched on day of receiving order.

**BE** Taller in 14 days or money back. Details, 1d.—Stebbing's System, 28 (HB) Dean Road, London, N.W.2.

**£5** to £20 weekly earned at home, running your own Mail Order business. Details, 1d.—Stebbing Publications Ltd. (HB), Naphill, High Wycombe.

**AMERICAN** Magazines post free for one year. Popular Mechanics, 32/-; Popular Science, 28/6; Mechanix Illustrated, 22/6; Popular Homecraft, 18/-; stamp for full list of others.—Willen Ltd. (Dept. 57), 101 Fleet Street, London, E.C.4.

**PLYWOOD** and Timber Offcuts for sale at very cheap prices. Veneered Oak plywood panels, etc., Japanese Oak, Bumper list, 1d. S.A.E.—Dept. 'H' JDD, Storage, 71 Northcross Road, S.E.22. Tel.: BR1xton 7441.

**STAMPS** free. Wonderful offer. Approvals from 3d.—Walker, 13 Broom Rd., Hale, Cheshire.

**2/6** South Africa Stamp free. Stamp brings pictorial approvals.—G. Smith, P.T.S., 95 Ocean Road, South Shields.

**CV102** Crystal diode. New, guaranteed, 3/6, postage 2½d. Fixing brackets, 3d. Recommended for 'Hobbies' crystal set; wiring instructions for reliable set. Send stamp for lists, including copper wires, enamelled, silk, cotton covered; B.A. screws, nuts, washers; headphones, radio publications; Paxolin type tubes, ebonite and bakelite panels, rods, etc.—P.R.S., 33 Bourne Gardens, London, E.4.

**MECHANICAL** Wood Toy-maker—a new book with 158 illustrations and patterns, 2/6. Lead Toy Casting slush and gravity, with 128 illustrations and catalogue of moulds, 2/6.—G. F. Rhead, 2 Waldegrave Park, Twickenham.

**PLYWOOD** Offcut parcels, nothing under 12×12×½ in., 15 sq. ft. parcels, 7/6, post paid. Immediate despatch.—Breezcraft Limited, 113 High Street, Staines, 3461/2.

**LEARN** Self-defence quickly or money back. Details of Wharton Course, 1d.—Stebbing Publications (H), 28 Dean Road, London, N.W.2.

**LAY** your own solid or ply Parquet floors, over existing wood floors. Materials supplied complete with instructions. Wall panelling, polishes, etc. Call or write—New-Een (H), 101 King's Cross Road, London, W.C.1.

**STAMP** Albums, Outfits, accessories, etc. Lists, 3d.—R. Hawkins (Dept. L2), 247 Rotherhithe New Road, S.E.16.

**USE** spare time on profitable homework, making fancy goods. Write for free booklet.—(Area 544), 54 Southgate Street, Leicester.

**HARDWOOD** Ball Beads, ½ in. diameter, suitable for children's counting frames, etc. 5/3 per hundred, plus 1/9 P.T.—Joyden Toy Co., 193 Chase Side, London, N.14.

**HOME** Watch and Clock Repair Outfit. Includes watchmaker's magnifying eyeglass, tweezers, screwdrivers, oilers, oil, brush, dusting powder, plus illustrated explanatory book. Watch and clock repairing simplified. In container, 12/9 inclusive.—D. Bolster (Dept. H), 5a Station Parade, Ashford, Middx.

**HOMEWORKERS** required, either sex, light Assembly. Part or full time. S.A.E.—Esprey, Box 18, 41 Wade Street, Lichfield.

**LOVELY!** Then write Secretary U.C.C., 55B.B. Hay St., Braughing, Herts. Genuine. Est. 1905.

**LOOK!** All at 3/—Metal Die Cast Moulds for toy making. Soldiers, planes, sailors, ships and farm-yard stock, etc. All new lines. Pick where you like, 3/- each mould. New illustrated Catalogue, price 6d., post free.—Robin Hood Moulds (Dept. H), 140 Hollings Road, Bradford, Yorks.

**MADE** big money, so can you. Enclose envelope.—H. Wamsteker, Box 34, Wynberg, Cape, Africa.

**START** earning money at home, whole or spare time, making up fancy leather and felt goods. Material provided. Write for rates of pay, etc.—Grange Co., 2 Curzon Street, Leicester.

**STAMPS.** 25-1d. 50-2d., etc. Approva Books. Free gift.—Pavely, 12 Leeder Close, Coventry.

**LEARN** Perspex modelling the practical way, by making the toast rack, cigarette/trinket box, brooches and bracelets featured in our latest course. (Details, 6d.) Instructional course, 29/11.—Plastics Home Products, 18 St. Mary's Road, London, N.9.

**BEAUTIFUL** interior decorating for walls, ceilings, etc. in mottle roughcast, etc., can be obtained by using 20th Century Plastic. In all pastel shades, price 9/6 per 6lbs. (delivered). Sample, 1/6.—20th Century Products (1), 99 King's Cross Road, London, W.C.1.

**NEW** Zealand 6 free. 2½d. stamp for approvals.—D. Bailey, 72 Marshfield Road, Goole, Yorks.

**NEW** Zealand stamps free. 15 different. Send 3d. postage and request approvals.—Crutchfield, 11 West Court Street, Brompton, Chatham.

**50** GOOD stamps free, mainly pictorial. Send for approvals, enclosing 2½d. Junior or medium.—Beeze, 116 Newton Rd., Mumbles, Swansea.

**MAKE** dioramas. Fascinating, profitable. Design and instructions, 3/6.—BCM/EASIPLAN, London, W.C.1.

**MATCHBOX** radio. With the aid of our instructions, you can build a complete radio set in a matchbox, using parts purchased from your radio dealer. The set incorporates medium wave inductor with station selector switch, long wave loading coil, and crystal-valve radar detector. Powered entirely by the incoming signal, no batteries are required. Full instructions, drawings, and theoretical circuit diagram. Price 3/—, post free.—Swift Radio (H), 137 Cotham Brow, Bristol 6. Mail order only.

**FREE** stamps value 1/- pick your own. Send 2½d. for approvals, stamps from 3d. each, large Pictorials, Diamonds, Triangulars, etc. Space fillers 12 a penny. Liberal discounts.—Carlless, 10 Henderson Road, Easney, Portsmouth.

**MAKE** your own Jig-saw Puzzles. Fine Art Pictures, various reproductions and sizes. Also suitable for framing. Stamp for full list.—Joyden Toy Co., 193 Chase Side, London, N.14.

**FOR** sale—Hornby clockwork engine Royal Scot, length 16ins., four coaches, six wagons, thirty-six rails, points, turn-table. All good condition, scarcely used. Post paid, £5.—Mrs. Peacock, 30 High Street, Halstead, Essex.

**HAVE** you got your Juneero Riveting Jig yet? If from all hobby shops or post free from—Juneero Ltd., Stirling Corner, Boreham Wood, Herts.

**LUMINOUS** Paint. 2/- per tin. Box No. 44, Hobbies Weekly, Dereham, Norfolk.

**STAMPS** free—Empire packet including Pictorials and Victorians free to approval applicants.—Robert J. Peck, 7A Kemp Road, Bournemouth, Hants.

**MAKE** magic X-ray mirrors. You see through, but they can't see you. This amazing device is an ordinary mirror one side, but you can see through the other side. Complete process and directions for making these novel X-ray mirrors, 10/— Complete lead toy making course, 6/3. How to grow dwarf trees, full instructions, 2/6. Spare-time pounds, how to profit from your free hours, 2/9. Deal in stamps, explains the profitable stamp trade, 2/9. All American magazines available by subscription, single copy or library. Big list of books on approval, details from—Herga Limited, 394 Waverley House, Hastings.

**STAMP** collectors. Two giant Pictorials free to Applicants for progressive discount approvals. Postal business only.—Willson Tilley, 279 London Road, Rainham, Gillingham, Kent.

**STAMPS FREE!** Twenty unused (2½d.)—S.G. H. Barnett, Limington, Somerset.

**HUNDREDS** of tested money makers. Complete book, 2/6, post paid. Business secrets, formulas, mail order, ideas, etc., no fees or catches. Money returned if dissatisfied.—H.W., 98 Mayplace Road East, Barnehurst, Kent.

**NO** catch, absolutely free. Large 2/6 South Africa stamp. Request approvals, enclose 3d. postage.—N. H. Dargue, 36a Gray Avenue, Murton, Co Durham.

**TELEVISION** Constructors Manual, 3/9. Build an inexpensive receiver with this practical handbook.—Blackshaw, BCM/HADOR, London, W.C.1.

**BEGINNERS.** New beautifully illustrated Balbum, 100 stamps and mounts, 3/— 200—4/-, 500—6/-, 1,000—10/— All different, World Pictorials, Mint.—W. Hewison, 16 Westwood, Scarborough.

**FREE** 8 scarce old Latvia stamps. Request approvals. Enclose 3d. postage.—N. H. Dargue, 36b Gray Avenue, Murton, Co Durham.

**STAMP** magnifier and 500 different World Stamps, 4/—H. Whitby, Godshill, Fordingbridge, Hants.

**INTRODUCTIONS.** Pen friends, companionship or marriage.—V.C.C., 34 Honeywell Road, London, S.W.11.

**IF** you have nothing to occupy your leisure, why not try something interesting and profitable? Experience is not required in leathercraft. Send S.A.E. for our brochure, free of obligation.—Leatheweave (Dist. 37), 2 Tudor Rd., Leicester.

**FREE** perforation gauge to all applicants for our approvals. Ideal for beginners and medium collectors. Send S.A.E. for trial selection.—Alan Archer, 14 Brookfield Avenue, Stenson Road, Derby.

**BOHEMIA** Red Cross stamp (cat. 9d.) and Bothers free. Request approvals. Enclose 3d. postage.—N. H. Dargue, 36c Gray Avenue, Murton, Co Durham.

**PERFORATION** gauge free. Send 2/6 for either 100 different British Colonials or 100 large Pictorials.—Selby, 66 Donnington Road, London, N.W.10.

**PERSONS** are wanted for spare time work, making up fancy goods at home. Experience unnecessary. Write for details.—Dept. 918, Universal Products, 5 Cornhill, Lincoln.

**WANTED** Design No. 2039.—E. Lodge, 9 Grove Road, Ash Vale, Aldershot, Hants.

**SPACE** fillers from 3 a 1d. upwards.—Jeffreys, 52 Bay View, Craigavon, Port Talbot.



## YOU CAN BECOME A HANDICRAFTS INSTRUCTOR

### EXPERIENCE NOT ESSENTIAL

Men who enjoy making things in wood or metal can turn their hobby into a permanent and interesting Career. Short hours, long holidays, and security in a job you would really enjoy, can be yours if you become a Handicrafts instructor. Let us send details of the easiest and quickest way to get the necessary qualification.

**We definitely guarantee  
"NO PASS—NO FEE"**

If you would like to know about our unique method of preparing you for one of these appointments, write today, and we will send you our informative 176 page Handbook—free and without obligation. Mark your letters "Handicrafts Instructor".

**BRITISH INSTITUTE OF  
ENGINEERING TECHNOLOGY**

595 Shakespeare House  
Stratford Place, London, W.1

# BIET




## BRITFIX BALSA CEMENT

★ The ideal transparent cement for Balsa Ply Wood, Hard Woods, and Plastics, combining rapid drying with utmost tenacity.

Remember  
**STICK BY  
BRITFIX**

4oz. Tube 6d.  
1oz. Tube 9d.  
2 1/2oz. Tube 1/3

**THE HUMBER OIL CO. LTD., HULL**



### R.A.F. SIGNALLING LAMPS

For day or night use. New Ex-W.D. 12v. 4 1/2 in. lamp, adaptable to voltage. Morse trigger, view finder, polished mirror reflector, 6 1/2 ft. rubber flex and plug. In strong wooden box 10 1/2 x 8 x 7 1/2 ins. leather carrying handle. Adaptable as car, motorcycle, spot lamp, stage or studio spot light.

Post 1/6 **14/9**

### Complete Two-Way TELEPHONE SETS

No Battery Required—Sound Powered, New Ex-W.D. in original cartons. Microphone can be used as earphone, and earphone as microphone. Ideal as extension speaker or earphone for radio, intercom. for offices, kitchen, restaurant.

Post 1/6 **15/6** each

Illustrated catalogue free

**PRIDE & CLARKE LTD.,**


(P.W.) STOCKWELL ROAD, LONDON, S.W.9. BRI 6251



**EVERY CAR THAT PASSES  
YOU WILL FIND THE INDEX MARK  
ALPHABETICALLY ARRANGED IN  
WHERE'S THAT CAR FROM ?**

Price 6d.

from all Booksellers or from the Publishers (1d. postage)  
**RALEIGH PRESS, EXMOUTH**




## FRETWORK HANDFRAMES

—for the fretworker, model maker and handyman. Made by Hobbies. In various

sizes. Details and prices on application at any Branch of Hobbies Ltd. or

**HOBBIES LTD., DEREHAM, NORFOLK**



The ML8 Lathe—  
the Craftsman's  
Choice

## MYFORD

For both the home craftsman and the professional expert, the ML8 Woodworking Lathe (8" swing x 30") incorporates the most modern, up-to-date features.

Extra attachments enable sawing, grooving, planing, rebating, sanding, grinding, polishing, metal and plastic turning. The illustration shows a mahogany bowl being turned on the Rear Turning Attachment.

The ML8 Lathe (also available on steel cabinet stand) is sold through all leading Tool Merchants.

**Myford Engineering Co., Ltd.**  
Beeston - Nottingham

## STOP SMOKING

You can overcome the smoking habit in 3 days or money back. Safe, pleasant, permanent. The only scientific way. **No Will Power necessary.** "Conquered the habit in 2 1/2 days. Am delighted".—F.C. "Within 2 days I was free from the tobacco habit".—W.G. "Was a smoker for 2 years and broke the habit in 2 days".—F.N. "I haven't smoked a cigarette for 5 weeks".—J.E. "I used to smoke 20 a day... now I have no desire to smoke".—J.M. Recommended by "Health and Efficiency Magazine". Complete course 6/6. Details 1d. stamp. Sent under plain cover.—**STEBBINGS, 28 (H/99), Dean Road, London, N.W.2. Established 1928.**


## MONEY-MAKING BOOKS

**114 WAYS TO BE YOUR OWN BOSS**—114 Tested ways of earning a second income at home with little or no capital 5/6  
**MONEY FROM MAIL ORDER**—How to start and run a Mail Order business at home and earn pounds weekly 5/6  
**HOW I WRITE AND SELL THRILLERS**—By the author of 73 successful thrillers 4/6  
Catalogue of Money Making Books free.  
**STEBBING PUBLICATIONS LTD., 28 (H/99) Dean Road, London, N.W.2. Established 1928.**

SHIPS  
GALLEONS  
LOCOS  
HISTORIC &  
ARCHITECTURAL  
SUBJECTS  
ENGINEERING  
MOVING  
TOYS  
ETC.

**Micromodels**

TRADE MARK






Assembling Micro-model replicas of beautiful Mechanical, Architectural, Industrial and Maritime Subjects has become a serious cult. On special cards, units readily shaped and assembled models authentic in every detail. Cost a few pence, often sell for guineas. Send 1d. stamp for Illustrated Descriptive Catalogue.  
**MICROMODELS LTD., 6 (H) Racquet Court, London, E.C.4**



# SMALL BLOCK TOY PATTERNS

See Front Page





STUDY  
AT  
HOME

IN YOUR  
SPARE  
TIME

# THE BENNETT COLLEGE

*will set you on the right  
course for success*

You make sure of planned progress in the career of your choice when you let the most progressive, most successful Correspondence College in the world coach you through the post. By friendly, individual training we equip you with the specialized knowledge you must have for a well-paid key position.  
Make the first move TODAY—post the coupon below!

**ALL TEXT BOOKS ARE  
FREE!** We send as many  
volumes as sub-  
ject chosen demands,  
they become your property.



## IS YOUR CAREER HERE? IF NOT, WRITE FOR FREE ADVICE

Accountancy Exams.  
Agriculture  
Applied Mechanics  
Auctioneers and  
Estate Agents  
Aviation (Engineering  
and Wireless)  
Blue Prints  
Boilers  
Book-keeping, Ac-  
countancy, and  
Modern Business  
Methods  
Builders' Quantities  
Building, Architec-  
ture, and Clerk of  
Works (A.R.I.B.A.  
Exams.)  
Carpentry and  
Joinery  
Chemistry  
Civil Engineering  
Civil Service  
All Commercial  
Subjects  
Commercial Art  
Common Prelim.  
E.J.E.B.  
Concrete and Struc-  
tural Engineering  
Diesel Engines  
Draughtsmanship.  
Electrical or  
Mechanical

Engineering.  
All branches. Sub-  
jects and Exams.  
General Certificate  
of Education  
Examinations  
General Education  
G.P.O. Eng. Dept.  
Heating and Ventila-  
tion  
Institute of Muni-  
cipal Engineers  
Journalism  
Languages  
Mathematics  
Metallurgy  
Mining: All Subjects  
Mining: Electrical  
Engineering  
Motor Engineering  
Naval Architecture  
Plastics  
Play Writing  
Plumbing  
Police, Special  
Course  
Preceptors,  
College of  
Press Tool Work  
Pumps and Pumping  
Machinery  
Quantity Surveying  
—Inst. of Quantity  
Surveyors Exams.

Radio Service En-  
gineering  
Radio (Short Wave)  
Road Making and  
Maintenance  
Salesmanship  
Sanitation  
School Attendance  
Officer  
Secretarial Exams.  
Sheet Metal Work  
Shipbuilding  
Shorthand (Pitman's)  
Short Story Writing  
Speaking in Public  
Structural Engineer-  
ing  
Surveying (R.I.C.S.  
Exams.)  
Teachers of Handi-  
crafts  
Telecommuni-  
cations (City and  
Guilds)  
Television  
Transport Inst.  
Examinations  
Viewers, Gaugers  
Inspectors  
Weights and Mea-  
sures Inspectors  
Wireless Telegraphy  
and Telephony  
Works Managers

## COUPON. CUT THIS OUT

IF YOU ATTEND TO THIS NOW  
IT MAY MAKE A WONDERFUL  
DIFFERENCE TO YOUR FUTURE.



To DEPT. 62  
THE BENNETT COLLEGE LTD.  
SHEFFIELD

Please send me (free of charge)

Particulars of .....

Your private advice

about .....

(Cross out line  
which does not  
apply.)

PLEASE WRITE IN BLOCK LETTERS

Name .....

Address .....

CASCO

# COLD water GLUES



*supersede this*

CASCO Glues are easily and quickly prepared for use, no heat being required. CASCO Glues comply with MODERN BRITISH STANDARDS SPECIFICATION requirements, ensuring outstanding strength and durability.  
CASCO Glue, Grade "A" is the world-famous Casein Cold Water Glue manufactured in Great Britain, Australia, U.S.A., Argentina and Scandinavian countries.  
Conforms to British Standards Specification 1444 Type A.



Stocked by Ironmongers, Builders' Merchants, Hardware Stores, etc.

### DISTRIBUTORS:


Gt. Britain: Charles Cleeve & Co. Ltd.  
45 Gt. Peter St., London, S.W.1.  
Eire: Waller & Willis Ltd.  
60 Middle Abbey St., Dublin  
M. J. Galligan, 16 Oliver Plunkett St., Cork



**FREE!** Send for literature and Free Sample to the manufacturers  
**LEICESTER, LOVELL & CO. LTD.**  
(Dept. HW) NORTH BADDESLEY, SOUTHAMPTON



## THE ECONOMICAL "CUB" FRACTIONAL



Standard Motor without feet

For every purpose in the  
small home workshop . . . .  
use a BROOK "CUB" 1/4 h.p.  
motor. Single or split phase.  
Electric motors from 0.25  
to 200 H.P.



IMPRESS WORKS MOTORS HUDDERSFIELD

I.H.M.150